

Section 1. Product and Company Identification

Product Name Mineral Spirits
CAS Number 8052-41-3

Parchem - fine & specialty chemicals
415 Huguenot Street
New Rochelle, NY 10801
📞 (914) 654-6800 📠 (914) 654-6899
🌐 parchem.com ✉ info@parchem.com

EMERGENCY RESPONSE NUMBER
CHEMTEL
Toll Free US & Canada: 1 (800) 255-3924
All other Origins: 1 (813) 248-0585
Collect Calls Accepted

Section 2. Hazards Identification

Classification of the substance or mixture

Flammable liquid: Category 3.

Carcinogen: Category 2. Specific target organ toxicant (central nervous system): Category 3.

Aspiration toxicant: Category 1. Product contains a Category 2 carcinogen at concentration between 0.1 and 1.0% wt. and is assigned a hazard classification on that basis. The associated label elements and product label information are optional and not included.

GHS Label Elements

Pictograms:



Signal word: DANGER

Hazard and precautionary statements

Hazard Statements

H226: Flammable liquid and vapor.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

Precautionary Statements

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233: Keep container tightly closed.

P240: Ground / bond container and receiving equipment.

P241: Use explosion-proof electrical, ventilating, and lighting equipment.

P242: Use only non-sparking tools.



P243: Take precautionary measures against static discharge.
P261: Avoid breathing mist/vapors.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313: IF exposed or concerned: Get medical advice/ attention.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P331: Do NOT induce vomiting.
P370 + P378: In case of fire: Use water fog, foam, dry chemical, or carbon dioxide (CO₂) to extinguish.
P391: Collect spillage.
P403 + P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.
P501: Dispose of contents and container in accordance with local regulations.

Hazard Not Otherwise Classified (HNOC): None as defined under 29 CFR 1900.1200.

Physical/Chemical Hazards: Material can accumulate static charges which may cause an ignition. Material can release vapors that readily form flammable mixtures. Vapor accumulation could flash and/or explode if ignited.

Health Hazards: May be irritating to the eyes, nose, throat, and lungs. Repeated exposure may cause skin dryness or cracking. May cause central nervous system depression.

Environmental Hazards: Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment

HMIS Rating

Health: 1*

Flammability: 2

Reactivity: 0

NFPA Rating

Health: 1*

Flammability: 2

Reactivity: 0



Section 3. Composition / Information on Ingredients

Common Name Mineral Spirits
Synonym(s) Petroleum Hydrocarbons
CAS Number 8052-41-3

COMPONENT	CAS NUMBER	CONCENTRATION
Mineral Spirits	8052-41-3	100%

Hazardous Constituent(s) Contained in Complex Substance(s) required for disclosure

Component	CAS Number	Percentage
Ethyl Benzene	100-41-4	0.1 – 0.5%
Naphthalene	91-20-3	0.1 – 0.5%
Nonane	111-84-2	1 – 5%
Pseudocumene (1,2,4-Trimethylbenzene)	95-63-6	1 – 5%
Toluene	108-88-3	0.1 – 1%

Section 4. First Aid Measures

Inhalation: Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Skin Contact: Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.

Eye Contact: Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion: Seek immediate medical attention. Do not induce vomiting.

Note to Physician: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately

Section 5. Firefighting Measures

Extinguishing Media

Appropriate Extinguishing Media: Use water fog, foam, dry chemical, or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water

Firefighting

Firefighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.



Unusual Fire Hazards: Vapors are flammable and heavier than air. Vapors may *travel* across the ground and reach remote ignition sources causing a flashback fire danger. Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

Hazardous Combustion Products: Oxides of carbon, Incomplete combustion products, Smoke, Fume

Flammability Properties

Flash Point: 43°C (109°F)

Flammable Limits (Approximate volume% in air): LEL: 0.7

Autoignition Temperature: 240°C (464°F)

Section 6. Accidental Release Measures

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800)424-8802.

Protective Measures

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 5 for firefighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: half-face or full-face respirator with filter(s) for organic vapor and, when applicable, H₂S, or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated SCBA is recommended. Work gloves that are resistant to aromatic hydrocarbons are recommended. Note: Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible.

Small spills: Normal antistatic work clothes are usually adequate.

Large spills: full body suit or chemical resistant, antistatic material is recommended.

Spill Management

Land Spill: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do it without risk. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements, or confined areas. A vapor suppressing foam may be used to reduce vapors. Use clean, non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Large Spills: Water spray may reduce vapor; but may not prevent ignition in closed spaces. Recover by pumping or with suitable absorbent.



Water Spill: Stop leak if you can do it without risk. Eliminate sources of ignition. Warn other shipping. If the Flash Point exceeds the Ambient Temperature by 10 degrees or more, use containment booms and remove from the surface by skimming or with suitable absorbents when conditions permit. If the Flash Point does not exceed the Ambient Air Temperature by at least 1 OC, use booms as a barrier to protect shorelines and allow material to evaporate. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

Environmental Precautions

Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

Section 7. Handling and Storage

Handling

Avoid all personal contact. Potentially toxic/irritating fumes/vapors may be evolved from heated or agitated material. Use only with adequate ventilation. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Loading/Unloading Temperature: [Ambient]

Transport Temperature: [Ambient]

Transport Pressure: [Ambient]

Static Accumulator: This material is a static accumulator. A liquid is typically considered a nonconductive, static accumulator if its conductivity is below 100 pS/m (100x10E-12 Siemens per meter) and is considered a semi-conductive, static accumulator if its conductivity is below 10,000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, anti-static additives, and filtration can greatly influence the conductivity of a liquid.

Storage:

The container choice, for example storage vessel, may affect static accumulation and dissipation. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Storage containers should be grounded and



bonded. Fixed storage containers, transfer containers and associated equipment should be grounded and bonded to prevent accumulation of static charge.

Storage Temperature: [Ambient]

Storage Pressure: [Ambient]

Suitable Containers/Packing: Drums; Barges; Tank Cars; Tank Trucks

Suitable Materials and Coatings (Chemical Compatibility): Carbon Steel; Polyethylene; Polypropylene; Teflon; Stainless Steel; Polyester

Unsuitable Materials and Coatings: Polystyrene; Natural Rubber; Butyl Rubber; Ethylene-propylene-diene monomer (EPDM)

Section 8. Exposure Controls / Personal Protection

Exposure Limit Values

Exposure Limits/Standards (Note: Exposure limits are not Additive)

Substance Name	Form	Limit/Standard			NOTE	Source
Ethyl benzene		TWA	435 mg/m ³	100 ppm	N/A	OSHAZ1
Ethyl benzene		TWA	20 ppm		N/A	ACGIH
Naphthalene		TWA	50 mg/m ³	10 ppm	N/A	OSHAZ1
Naphthalene		TWA	10 ppm		Skin	ACGIH
Nonane		TWA	200 ppm		N/A	ACGIH
Pseudocumene (1,2,4-trimethylbenzene)		TWA	25 ppm		N/A	ACGIH
Mineral Spirits		TWA	2900 mg/m ³	500 ppm	N/A	OSHAZ1
Mineral Spirits	Vapor.	TWA	66 ppm	400 mg/m ³	Total Hydrocarbons	
Mineral Spirits		TWA	100 ppm		N/A	ACGIH
Toluene		Ceiling	300 ppm		N/A	OSHAZ2
Toluene		Maximum Concentration	500 ppm		N/A	OSHAZ2



Toluene		TWA	200 ppm		N/A	OSHAZ2
Toluene		TWA	20 ppm		N/A	ACGIH

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

Biological limits

Substance	Specimen	Sampling Time	Limit	Determinant	Source
Ethyl Benzene	Creatine in urine	End of shift	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	ACGIH BELs (BEIs)
		End of shift	Not assigned	1-Maphthol with hydrolysis + 2-Naphthol, with hydrolysis	ACGIH BELs (BEIs)
		Prior to last shift of work week	0.02 mg/L	Toluene	ACGIH BELs (BEIs)
		End of shift	0.3 mg/g	o-Cresol, with hydrolysis	ACGIH BELs (BEIs)
		End of shift	0.03 mg/L	Toluene	ACGIH BELs (BEIs)

Engineering Controls: The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

Control measures to consider: Adequate ventilation should be provided so that exposure limits are not exceeded. Use Explosion-proof ventilation equipment.

Personal Protection

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Half-face filter respirator

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen



levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include: Chemical resistant gloves are recommended.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include: Chemical/oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Environmental Controls: Comply with applicable environmental regulations limiting discharging to air, water, and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

Section 9. Physical and Chemical Properties

Note: Physical and chemical properties are provided for safety, health, and environmental considerations only and may not fully represent product specifications. Contact the supplier for additional information.

Physical State: Liquid

Form: Clear

Color: Colorless

Odor: Petroleum/Solvent

Odor Threshold: N/D

Relative Density (at 15.6°C): 0.79

Density: 789 kg/m³ (6.58 lbs/gal, 0.79 kg/dm³)

Flammability (Solid, Gas): N/A

Flash Point: 43°C (109°F)

Flammable Limits (Approximate volume% in air): LEL: 0.7 UEL: 5.6

Auto-ignition Temperature: 240°C (464°F)

Boiling Point/ Range: 158 - 204°C (316 - 399°F)

Decomposition Temperature: N/D

Vapor Density (Air = 1): 5 at 101 kPa

Vapor Pressure: 0.161 kPa (1.21 mm Hg) at 20°C | 0.9 kPa (6.75 mm Hg) at 38°C

Evaporation Rate (n-Butyl Acetate= 1): 0.14

pH: N/A

Log Pow (n-Octanol/Water Partition Coefficient): N/D

Solubility in Water: Negligible



Viscosity: 1.02 cSt (1.02 mm²/sec) at 40°C | 1.23 cSt (1.23 mm²/sec) at 25°C

Oxidizing Properties: See Hazards Identification Section.

Other Information

Freezing Point: N/D

Melting Point: N/D

Pour Point: < -51°C (-60°F)

Molecular Weight: 145

Coefficient of Thermal Expansion: 0.00074 VNDEGC

Section 10. Stability and Reactivity

Reactivity: See sub-sections below.

Stability: Material is stable under normal conditions.

Conditions to Avoid: Avoid heat, sparks, open flames, and other ignition sources.

Materials to Avoid: Strong oxidizers

Hazardous Decomposition Products: Material does not decompose at ambient temperatures.

Possibility of Hazardous Reactions: Hazardous polymerization will occur

Section 11. Toxicological Information

Information on toxicological effects

Hazard Class	Conclusion/Remarks
Inhalation	
Acute toxicity (Rat): 4 hour(s) LC50 > 13.1 mg/L (Max attainable vapor conc.)	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guidelines 403
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
Ingestion	
Acute Toxicity (Rat): LD50 > 15000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 401
Skin	
Acute Toxicity (Rabbit): LD50 > 3400 mg/kg	Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402
Skin Corrosion/Irritation: Data available.	May dry the skin leading to discomfort and dermatitis. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404



Eye	
Serious Eye Damage/Irritation: Data available	May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405
Sensitization	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: Data available.	Not expected to be a skin sensitizer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406
Aspiration: Data available.	May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material.
Germ Cell Mutagenicity: Data available.	Not expected to be a germ cell mutagen. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 473 474 475 479
Carcinogenicity: No end point data for material.	Contains a substance that may cause cancer. Based on assessment of the components.
Reproductive Toxicity: Data available.	Not expected to be a reproductive toxicant. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 416 421 422
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for material.	May cause drowsiness or dizziness.
Repeated Exposure: Data available.	Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 408 411 413

Toxicity for Substances

Name	Acute Toxicity
Ethyl Benzene	Inhalation Lethality: 4 hours(s) LC50 17.8 mg/L (Vapor) (Rat); Oral Lethality: LD50 3.5 g/kg (Rat)



Naphthalene	Inhalation Lethality: 4 hour(s) LC50 > 0.4 mg/L (Max attainable vapor conc.) (Rat); Oral Lethality: LD50 533 mg/kg (Mouse)
-------------	--

Other Information

For the product itself: Vapor/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other neutral nervous system effects including death.

Prolonged and/or repeated skin contact with low viscosity materials may defeat the skin resulting in possible irritation and dermatitis.

Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Contains:

NAPHTHALENE: Exposure to high concentrations of naphthalene may cause destruction of red blood cells, anemia, and cataracts. Naphthalene caused cancer in laboratory animal studies, but the relevance of these findings to humans is uncertain.

ETHYLBENZENE: Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain.

The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
NAPHTHALENE	91-20-3	2,5
ETHYL BENZENE	100-41-4	5

Regulatory Lists Searched

- 1 = NTP CARC
- 2 = NTP SUS
- 3 = IARC 1
- 4 = IARC 2A
- 5 = IARC 2B
- 6 = OSHA CARC

Section 12. Ecological Information

The information given is based on data available for the material, the components of the material, and similar materials.

Ecotoxicity: Material -- Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Mobility: Material-- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.



Persistence and Degradability

Biodegradation: Material - Expected to be inherently biodegradable.

Hydrolysis: Material- Transformation due to hydrolysis not expected to be significant.

Photolysis: Material- Transformation due to photolysis not expected to be significant.

Atmospheric Oxidation: Material - Expected to degrade rapidly in air

Other Ecological Information

VOC (EPA Method 24): 6.593 lbs/gal

Section 13. Disposal Considerations

Waste Treatment Methods: Dispose of product and contaminated packaging in accordance with all local, state, and federal environmental control regulations.

Section 14. Transport Information

Land (DOT)

Proper Shipping Name: Petroleum Distillates, N.O.S. (1,2,4-Trimethylbenzene)

Hazard Class & Division: 3

ID Number: 1268

Packing Group: III

Marine Pollutant: Yes

ERG Number: 128

Label(s): 3

Transport Document Name: UN1268, Petroleum Distillates, N.O.S. (1,2,4-Trimethylbenzene), 3, PG III, Marine Pollutant

Land (TOG)

Proper Shipping Name: Petroleum Distillates, N.O.S.

Hazard Class & Division: 3

UN Number: 1268

Packing Group: III

Marine Pollutant: Yes

Footnote: Marine Pollutant designation is applicable only if shipped over water.

Sea (IMDG)

Proper Shipping Name: Petroleum Distillates, N.O.S. (1,2,4-Trimethylbenzene)

Hazard Class & Division: 3

EMS Number: F-E, S-E

UN Number: 1268

Packing Group: III

Marine Pollutant: Yes

Label(s): 3



Transport Document Name: UN1268, Petroleum Distillates, N.O.S. (1,2,4-Trimethylbenzene), 3, PG III, (43°C c.c.), Marine Pollutant

AIR (IATA)

Proper Shipping Name: Petroleum Distillates, N.O.S.

Hazard Class & Division: 3

UN Number: 1268

Packing Group: III

Label(s) I Mark(s): 3

Transport Document Name: UN1268, Petroleum Distillates, N.O.S., 3, PG III

Section 15. Regulatory Information

OSHA Hazard Communication Standard: This material is considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200.

Listed or exempt from listing/notification on the following chemical inventories: AICS, DSL, IECSC, KECI, PICCS, TSCA

EPCRA Section 302: This material contains no extremely hazardous substances.

CERCLA: This material is not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA). Contact local authorities to determine if other reporting requirements apply.

CWA/OPA: This product is classified as an oil under Section 311 of the Clean Water Act (40 CFR 110) and the Oil Pollution Act of 1990. Discharge or spills which produce a visible sheen on either surface water, or in waterways/sewers which lead to surface water, must be reported to the National Response Center at 800-424-8802.

SARA (311/312) Reportable Hazard Categories: Fire. Immediate Health. Delayed Health.

SARA (313) Toxic Release Inventory:

Chemical Name	CAS Number	Typical Value
Pseudocumene (1,2,4-Trimethylbenzene)	95-63-6	1 - 5%
Naphthalene	91-20-3	0.1 - 0.5%
Ethyl Benzene	100-41-4	0.1 - 0.5%

The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
Ethyl Benzene	100-41-4	1,4,10,17,19
Naphthalene	91-20-3	1,4,10,17,19



Nonane	111-84-2	1,5,9,13,16,17,18
Pseudocumene (1,2,4-Trimethylbenzene)	95-63-6	1,13,16,17,18,19
Mineral Spirits	8052-41-3	1,4,13,16,17,18
Toluene	108-88-3	15,17,19
Xylenes	1330-20-7	1,4,15,19

Regulatory Lists Searched

- 1 = ACGIH ALL
- 2 = ACGIH A1
- 3 = ACGIH A2
- 4 = OSHA Z
- 5 = TSCA 4
- 6 = TSCA 5a2
- 7 = TSCA 5e
- 8 = TSCA 6
- 9 = TSCA 12b
- 10 = CA P65 CARC
- 11 = CA P65 REPRO
- 12 = CA RTK
- 13 = IL RTK
- 14 = LA RTK
- 15 = MI 293
- 16 = MN RTK
- 17 = NJ RTK
- 18 = PA RTK
- 19 = RI RTK

Code key: CARC=Carcinogen; REPRO=Reproductive

Section 16. Other Information

Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product.

REVISION DATE: 6/8/2016